

# VERTO SQUARE EDGE CCT

SLI003074CCT\_PW



|                    |                         |                           |              |
|--------------------|-------------------------|---------------------------|--------------|
| Power              | <b>10 W</b>             | Voltage                   | <b>230 V</b> |
| Colour temperature | <b>2700/4000/6000 K</b> | Colour of light           | <b>CCT</b>   |
| Beam angle         | <b>160/120 °</b>        | Degree of protection (IP) | <b>IP65</b>  |

## Technical data

## Logistics data

|                           |                                                    |
|---------------------------|----------------------------------------------------|
| Code                      | SLI003074CCT_PW                                    |
| Power                     | 10 W                                               |
| Nominal current           | 80 mA                                              |
| Voltage                   | 230 V                                              |
| Energy consumption        | 10 kWh/1000h                                       |
| Frequency                 | 50HZ Hz                                            |
| Protection class          | II                                                 |
| Power factor              | 0.500000                                           |
| Useful luminous flux*     | 1200 lm (360°)                                     |
| Luminous flux**           | 700 lm (360°)                                      |
| Lamp efficacy             | 120 lm/W                                           |
| Colour temperature        | 2700/4000/6000 K                                   |
| Colour of light           | CCT                                                |
| Beam angle                | 160/120 °                                          |
| RA                        | 80                                                 |
| Light source included     | +                                                  |
| Dimmable                  | No                                                 |
| Working temperature range | -20/+40 °                                          |
| Warranty                  | 2 years                                            |
| Lifespan                  | 17000 h                                            |
| (On/Off)                  | 15000                                              |
| Housing material          | Plastic                                            |
| Degree of protection (IP) | IP65                                               |
| Colour                    | Black                                              |
| Dimension (AxBxC)         | 160x160x100 mm                                     |
| For use                   | Inside/Outside                                     |
| Assembly method           | On the ceiling                                     |
| Application               | INT/EXT                                            |
| Made in                   | PRC                                                |
| Other                     | Light color change function<br>2700K/4000K/6000K , |

|                       |          |
|-----------------------|----------|
| Bulk packaging        | 20 pcs.  |
| Quantity per pallet   | 320 pcs. |
| Gross weight (1 pcs.) | 0.52 kg  |

## Related documents



 Declaration of Conformity

