

# STREETOS 3

SLI027024NW\_PW

STREETOS 2 STREETLIGHT 150W NW 230V 145/75deg IP65 IK09 675x218x124mm 5Y WARRANTY



|                           |                 |
|---------------------------|-----------------|
| Power                     | <b>150 W</b>    |
| Colour temperature        | <b>4000 K</b>   |
| Beam angle                | <b>145/75 °</b> |
| Degree of protection (IP) | <b>IP65</b>     |

|                 |                      |
|-----------------|----------------------|
| Voltage         | <b>230 V</b>         |
| Colour of light | <b>Neutral white</b> |
| IK              | <b>9</b>             |

## Technical data

|                              |                 |
|------------------------------|-----------------|
| Code                         | SLI027024NW_PW  |
| Power                        | 150 W           |
| Nominal current              | 660 mA          |
| Voltage                      | 230 V           |
| Energy consumption           | 150 kWh/1000h   |
| Frequency                    | 50HZ Hz         |
| Protection class             | I               |
| Power factor                 | 0.9             |
| Useful luminous flux*        | 21000 lm (360°) |
| Luminous flux                | 20250 lm (360°) |
| Lamp efficacy                | 140 lm/W        |
| Colour temperature           | 4000 K          |
| Colour of light              | Neutral white   |
| Beam angle                   | 145/75 °        |
| RA                           | 70              |
| Light source included        | Yes             |
| Uniformity of color SDCM max | 5               |
| Dimmable                     | No              |
| Working temperature range    | -20/+40 °       |
| Warranty                     | 5 years         |
| Lifespan                     | 50000 h         |
| (On/Off)                     | 25000           |
| Housing material             | aluminum        |
| IK                           | 9               |
| Degree of protection (IP)    | IP65            |
| Colour                       | Szary           |
| Dimension (AxBxC)            | 675x218x124 mm  |
| Mounting hole                | 60 mm           |
| For use                      | Outside         |
| Assembly method              | na słup         |
| Made in                      | PRC             |
| Other                        | 100-277V ,      |

## Logistics data

|                     |         |
|---------------------|---------|
| Bulk packaging      | 4 pcs.  |
| Quantity per pallet | 80 pcs. |

\*applies to the LED source used

## Related documents



 User manual



 Declaration of  
Conformity

