

SLI048010NW_PW

SLI048010NW_PW

HALLS LINE 3 HIGH BAY 75W NW 230V 60X90DEG IP66 IK10 440X130X115MM BLACK 5Y WARRANTY 1-10V



Power	75 W	Voltage	230 V
Luminous flux*	12375 lm (360°)	Colour temperature	4000 K
Colour of light	Neutral white	Beam angle	60x90 °
IK	10	Degree of protection (IP)	IP66

Technical data

Logistics data

Code	SLI048010NW_PW
Power	75 W
Nominal current	350 mA
Voltage	230 V
Energy consumption	75 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	Yes
Power factor	0.95
Useful luminous flux*	12375 lm (360°)
Luminous flux**	12000 lm (360°)
Lamp efficacy	165 lm/W
Luminous intensity	11300 cd
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	60x90 °
RA	80
Light source included	Yes
Dimmable	Yes
Working temperature range	-20 +40 °
Lifespan	50000 h
Housing material	Aluminum
IK	10
Degree of protection (IP)	IP66
Colour	Black
Dimension (AxBxC)	440x130x115 mm
For use	Outside / Inside
Assembly method	Suspended
Whether it should work in conditions other than normal	Yes
Made in	PRC

Quantity per pallet	88 pcs.
Gross weight (1 pcs.)	2.9 kg

Related documents

 User manual