

SLI048011NW_PW

SLI048011NW_PW

HALLS LINE 3 HIGH BAY 150W NW 230V 60X90DEG IP66 IK10 795X130X115MM BLACK 5Y WARRANTY 1-10V



Power	150 W
Luminous flux*	24750 lm (360°)
Colour of light	Neutral white
IK	10

Voltage	230 V
Colour temperature	4000 K
Beam angle	60x90 °
Degree of protection (IP)	IP66

Technical data

Logistics data

Code	SLI048011NW_PW
Power	150 W
Nominal current	680 mA
Voltage	230 V
Energy consumption	150 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	Yes
Power factor	0.95
Useful luminous flux*	24750 lm (360°)
Luminous flux**	24000 lm (360°)
Lamp efficacy	165 lm/W
Luminous intensity	22500 cd
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	60x90 °
RA	80
Light source included	Yes
Dimmable	Yes
Working temperature range	-20 +40 °
Lifespan	50000 h
Housing material	Aluminum
IK	10
Degree of protection (IP)	IP66
Colour	Black
Dimension (AxBxC)	795x130x115 mm
For use	Outside / Inside
Assembly method	Suspended
Whether it should work in conditions other than normal	Yes
Made in	PRC
Other	Zaw. 2 źródła św. o EEI D, Fi use=12375lm, P=75W ,

Quantity per pallet	60 pcs.
Gross weight (1 pcs.)	4.7 kg

Related documents

 User manual