


WLD+40091_CCT



Power	20 W
Colour temperature	2700/3300/4000 K
Beam angle	24 °

Voltage	48 V
Colour of light	CCT
Degree of protection (IP)	IP20

Technical data

Logistics data

Code	WLD+40091_CCT
Power	20 W
Nominal current	417 mA
Voltage	48 V
Energy efficiency class	F
Energy consumption	20 kWh/1000h
Frequency	DC Hz
Protection class	III
Power factor	1
Useful luminous flux*	2100 lm (360°)
Luminous flux	1300 lm (360°)
Lamp efficacy	105 lm/W
Luminous intensity	8500 cd
Colour temperature	2700/3300/4000 K
Colour of light	CCT
Beam angle	24 °
RA	90
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 to +40 °
Warranty	5 years
Lifespan	50000 h
(On/Off)	25000
Housing material	aluminum
Degree of protection (IP)	IP20
Colour	Czarny
Dimension (AxBxC)	65x140 mm
For use	Inside
Assembly method	on track 48V
Made in	PRC
Other	CCT ,

Bulk packaging	30 pcs.
Quantity per pallet	270 pcs.

*applies to the LED source used