

LED AR111 GU10

W0J+16984

LED source LED AR111 GU10 20 W with the popular GU10 mount. It is made of high-quality components, supported by a 5-year warranty. It also stands out for its very high colour rendering index RA>90. Narrow beam angle 30° gives directional light so that selected objects or surfaces can be better exposed.



Power	20 W	Voltage	230 V
Luminous flux**	1800 lm (360°)	Colour temperature	2700 K
Colour of light	WW	Beam angle	30 °
Socket	GU10		

Technical data

Code	WQJ+16984
Power	20 W
Nominal current	150 mA
Voltage	230 V
Energy efficiency class	F
Energy consumption	20 kWh/1000h
Frequency	50HZ Hz
Power supply included	+
Power factor	0.6
Useful luminous flux*	1600 lm (90°)
Luminous flux**	1800 lm (360°)
Lamp efficacy	80 lm/W
Luminous intensity	4600 cd
Colour temperature	2700 K
Colour of light	WW
Beam angle	30 °
RA	90
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 / +40 °
Lifespan	50000 h
Socket	GU10
Colour	White
Dimension (AxBxC)	111x78 mm
For use	Inside
Application	INT
Made in	PRC

Logistics data

Bulk packaging	50 pcs.
Quantity per pallet	1200 pcs.
Gross weight (1 pcs.)	0.16 kg

