

## Meaningful Innovation.

WEEE Number: 80133970

## **INSTRUCTION MANUAL**

### LED CEILING LAMP

#### **TECHNICAL DATA**

I LOTHINGAL DATA	
MODEL	VT-89015
SKU	24121
WATTS	3x6W
LUMENS	2160Lm
BEAM ANGLE	280°
CCT	3000K
MATERIAL	Steel+Aluminum+Acrylic
IP RATING	IP20
BASE SIZE	L500xW70xH30mm
DIMENSION	L685xW82xH211mm
INPUT POWER	AC: 220-240V, 50Hz





#### **INTRODUCTION & WARRANTY**

Thank you for selecting and buying V-TAC product. V-TAC will serve you the best. Please read these instructions carefully before starting the installing and keep this manual handy for future reference. If you have any another query, please contact our dealer or local vendor from whom you have purchased the product. They are trained and ready to serve you at the best. The warranty is valid for 2 years from the date of purchase. The warranty does not apply to damage caused by incorrect installation or abnormal wear and tear. The company gives no warranty against damage to any surface due to incorrect removal and installation of the product. The products are suitable for 10-12 Hours Daily operation. Usage of product for 24 Hours a day would void the warranty. This product is warranted for manufacturing defects only.

#### WARNING

- 1. Please make sure to turn off the power before starting the installation.
- 2. Installation must be performed by a qualified electrician.
- 3. The light source of this luminaire is not replaceable; when the light source reaches its end of life the whole luminaire shall be replaced.
- 4. Proper grounding should be ensured throughout the installation.
- 5. For Indoor Use only





## MULTI-LANGUAGE MANUAL QR CODE

Please scan the QR code to access the manual in multiple languages.



Points de collecte sur www.quefairedemesdechets.fr Privilégiez la réparation ou le don de votre appareil!




This marking indicates that this product should not be disposed of with other household wastes.



Caution, risk of electric shock.

#### **INSTALLATION INSTRUCTIONS**



- 1. Switch off the power before starting the installation.
- 2. Use screws to fix mounting bar to the junction box.
- 3. Make the wire connections with connectors.
  - Connect the live wire (L) from fitting to the live wire from main power supply.
  - Connect the neutral wire (N) from fitting to the neutral wire from main power supply.
  - Connect the earth wire from fitting to the earth wire from main power supply.
  - Please pay close attention and make sure the wires are not exposed outside when wiring connections.
- 4. Use screws to fix canopy to mounting bar.
- 5. Check if the installation is completed and turn on the power.

# 

V-TAC WEST EUROPE LTD. IN CASE OF ANY QUERY/ISSUE WITH THE PRODUCT, PLEASE REACH OUT TO US AT: SUPPORT@V-TAC.EU FOR MORE PRODUCTS RANGE, INQUIRY PLEASE CONTACT OUR DISTRIBUTOR OR NEAREST DEALERS. V-TAC WEST EUROPE LTD. GROUND FLOOR, 71 LOWER BAGGOT STREET, DUBLIN 02, IRELAND DO2 P593

**V-TAC UK LTD.** IN CASE OF ANY QUERY/ISSUE WITH THE PRODUCT PLEASE REACH OUT TO US AT SUPPORT@VTACEXPORTS.COM V-TAC, 5A TUNGSTEN PARK, DOWNS ROAD, WITNEY, OXFORDSHIRE, OX29 0AX